



# SIMPLE. INTUITIVE. POWERFUL.

## BENEFITS

- Conversations stay on track. Hear every nuance with the industry-leading sound quality, featuring Poly HD Voice
- Eliminate distracting background noise at the source with Poly Acoustic Fence and NoiseBlock AI
- Contacts and meetings are easily accessible, one tap away on a color touchscreen
- Easy for IT to manage with robust provisioning and management of telephony deployment and support
- Multiple headset options are available to suit any worker's style—in addition to the traditional handset

## POLY CCX 500

Meet the new standard in desktop touch screen phones. The Poly CCX 500 Business Media Phone has workers feeling confident they'll sound professional on every call. No word or inflection is missed, thanks to legendary audio quality, Poly HD Voice, and Poly Acoustic Clarity. And let's hear it for Poly Acoustic Fence. It eliminates background noise to keep calls quiet wherever it's noisy—like open offices and call centers.

By design, the phone is simple and intuitive to use—with one-touch-access to your contacts and meetings. So users can get right to work. IT will be a fan too. Robust provisioning and management capabilities take the headache out of telephony deployment and support. Looking for usability options? You got it. Choose a headset or handset. More options, more happiness.

- Models choices supporting Open SIP or native Microsoft Teams
- Color touchscreen operation with 5-inch multi-touch LCD display
- Hear every nuance with Poly HD Voice and Poly Acoustic Clarity
- Eliminate distracting background noise with Poly Acoustic Fence
- Full duplex speakerphone operation with world-class echo cancellation and Poly NoiseBlock AI
- Powerful chipsets to support next-generation features
- Headset options to suit any style (Bluetooth®, USB, RJ9)

# POLY CCX 500



Order headset separately

## SPECIFICATIONS

### USER INTERFACE FEATURES

- Gesture-based, multitouch-capable touchscreen
- 5-inch color LCD (720 x 1280 pixel)
- 9:16 aspect ratio
- Screensaver
- On-screen virtual keyboard
- Voicemail support
- Adjustable base height
- One USB type-A port (2.0 compliant) for media and storage applications
- One USB Type-C port (2.0 compliant) for media and storage applications
- Integrated Bluetooth 4.2
- Unicode UTF-8 character support
- Adjustable font size selection (regular, medium, large)
- Normal and dark mode
- Multilingual user interface<sup>1</sup> including Chinese, Danish, Dutch, English (Canada/US/UK), French, German, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Slovenian, Spanish, and Swedish

### AUDIO FEATURES

- Poly HD Voice technology delivers lifelike voice quality for each audio path: handset, hands-free speakerphone, and optional headset
- Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression
- Poly Acoustic Fence eliminates background noise when using a handset or wired headset
- Poly NoiseBlock AI removes most background noise when using the speakerphone even while you are talking
- TIA-920 wideband audio, type 1 compliant (IEEE 1329 full duplex)

- Frequency response—100 Hz–20 kHz for handset, optional headset, and handsfree speakerphone modes
- Codecs: G.711 (A-law and  $\mu$ -law), G.729AB, G.722 (HD Voice), G.722.1 iLBC
- Individual volume settings with visual feedback for each audio path
- Voice activity detection
- Comfort noise generation
- DTMF tone generation (RFC 2833 and in-band)
- Low delay audio packet transmission
- Adaptive jitter buffers
- Packet loss concealment
- OPUS support

### HEADSET AND HANDSET COMPATIBILITY

- Dedicated RJ-9 headset port
- Hearing aid compatibility to ITU-T P.370 and TIA 504A standards
- Compliant with ADA Section 508 Subpart B 1194.23 (all)
- Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids
- Compatible with commercially available TTY adapter equipment
- USB headset support
- Bluetooth headset support

### NETWORK AND PROVISIONING

- SIP protocol support
- SDP
- IETF SIP (RFC 3261 and companion RFCs)
- Two-port gigabit Ethernet switch
- 10/100/1000Base-TX across LAN and PC ports
- Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment

- Conforms to IEEE802.3-2002 (Clause 28) for link partner auto-negotiation
- Manual or dynamic host configuration protocol (DHCP) network setup
- Time and date synchronization using SNTP
- FTP/TFTP/HTTP/HTTPS server-based central provisioning for mass deployments
- Provisioning and call server redundancy supported<sup>1</sup>
- QoS Support—IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP
- VLAN—CDP, DHCP VLAN discovery, LLDP-MED for VLAN discovery - Network address translation support for static configuration and “keep-alive”
- SIP signaling
- RTCP and RTP support
- Event logging
- Syslog
- Hardware diagnostics
- Status and statistics reporting
- IPv4 and IPv6
- TCP
- UDP
- DNS-SRV

### SECURITY

- 802.1X authentication and EAPOL media encryption via SRTP
- Transport layer security (TLS)
- Encrypted configuration files
- Digest authentication
- Password login
- Support for URL syntax with password for boot server address
- HTTPS secure provisioning
- Support for signed software executables

# POLY CCX 500



## POWER

- Built-in auto sensing IEEE 802.3af Power over Ethernet (Class 0) 13 W (Max)
- External universal AC/DC adapter (optional) 48 VDC @ 0.52 A (25 W)
- ENERGY STAR® rated

## REGULATORY APPROVALS<sup>2</sup>

- Argentina ENACOM
- Australia RCM
- Brazil ANATEL
- Canada ICES and NRTL
- China SRRC
- China RoHS 2.0
- EEA CE Mark
- Eurasian Customs Union EAC
- India WPC
- Indonesia SDPPI
- Israel MOC
- Japan MIC and VCCI
- Malaysia SIRIM
- Mexico IFETEL and NYCE
- NZ Telepermit
- Saudi Arabia CITC
- Singapore IMDA
- South Africa ICASA
- South Korea KC
- Taiwan NCC
- UAE TRA
- USA FCC and NRTL

## RADIO

- USA–FCC Part 15.247
- Canada–RSS 247 Issue<sup>2</sup>
- EU–ETSI EN 300 328
- Japan–Article 2.1 Item 19-2
- Australia–AS/NZ4268

## SAFETY

- UL 62368-1
- CAN/CSA C22.2 No. 62368-1-14
- EN 62368-1
- IEC 60950-1 and IEC 62368-1
- AS/NZS 62368-1

## EMC

- FCC Part 15 Class B
- ICES-003 Class B
- EN 55032 Class B
- EN 55024
- EN 301 489-1 and EN 301 489-17
- CISPR32 Class B
- VCCI Class B

## OPERATING CONDITIONS

- Temperature: 0 to 40 °C (+32 to 104 °F)
- Relative humidity: 5% to 95%, noncondensing

## STORAGE TEMPERATURE

- -40 to +70 °C (-40 to +160 °F)

## POLY CCX 500 BUSINESS MEDIA PHONE SHIPS WITH

- Console
- Handset with handset cord (handset model only)
- Network (LAN) cable—CAT-5E
- Desk stand
- Setup sheet

## SIZE

- With handset: 17.8 cm x 21.6 cm x 5.2 cm WxHxD (7.0 in x 8.5 in x 2.0 in WxHxD)
- Without handset: 10.5 cm x 21.6 cm x 5.2 cm WxHxD (4.1 in x 8.5 in x 2.0 in WxHxD)

## PART NUMBERS

- 2200-49710-025 CCX 500 Business Media Phone without handset. Open SIP. PoE. Ships without power supply
- 2200-49720-025 CCX 500 Business Media Phone. Open SIP. PoE. Ships without power supply
- 2200-49720-019 CCX 500 Business Media Phone. Microsoft Teams/SFB. PoE. Ships without power supply
- 2200-49710-019 CCX 500 Business Media Phone without handset. Microsoft Teams/SFB. PoE. Ships without power supply
- 2200-49713-001 CCX 500 wall mount Kit

## WEIGHT

- CCX 500 with handset carton weight: 1.28 kg (2.82 lbs)
- CCX 500 without handset carton weight: 0.73 kg (1.61 lbs)

## MASTER CARTON QUANTITY

- Ten (10)

## WARRANTY

- One (1) year

<sup>1</sup> Planned localization

<sup>2</sup> Planned compliance

## LEARN MORE

For more information on CCX 500 visit [poly.com/ccx](https://poly.com/ccx)

©2021 Plantronics, Inc. All rights reserved. Poly and the propeller design are trademarks of Plantronics, Inc. The Bluetooth trademark is owned by Bluetooth SIG, Inc. and any use of the mark by Plantronics, Inc. is under license. All other trademarks are the property of their respective owners. 8.21 1255850